



**NOTES:**

1. INLET: TANK FITTING
2. OUTLET: 1/4" FLARE WITH BALL CHECK (2 PLCS)
3. GAUGE: 160# REG. GAUGE (2 PLCS)  
2000# TANK GAUGE
4. SAFETY BLOW-OFF: 130 ± 4 PSI
5. WORKING PRESSURE 0-120 PSI
6. POLY BONNET, RED

MATERIAL	NAME	DATE
	DRAWN	JRS 10/13/10
FINISH	ENG APPR.	
	<b>PROPRIETARY AND CONFIDENTIAL</b>	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



3248 NORTHWESTERN DR. SAN ANTONIO, TX 78238

TITLE:  
**REG, PRI, SODA, 2P2P, 160#,  
 TNK FTG, 1/4F-CV OUT, 2000#,  
 POLY, RED**

SIZE	DWG. NO.	REV
<b>A</b>	<b>T5752HP-02_SALES</b>	<b>A</b>

SCALE: 1:2      DO NOT SCALE DRAWING      SHEET 1 OF 1