


NOTES:

1. INLET: CO2 FITTING WITH CGA 320 NUT
2. OUTLET: 1/4" FLARE WITH CHECK
3. GAUGES: 160#, 2000#
4. SAFETY BLOW-OFF: 130 ± 4 PSI
5. WORKING PRESSURE: 0-120 PSI
6. BONNET: BLACK ZINC BONT
7. UL252: SERIES 3740

MATERIAL	NAME	DATE	 <small>2348 NORTHWESTERN DR. SAN ANTONIO, TX 78248</small>
	DRAWN	AMB	
FINISH	ENG APPR.		TITLE: REG, PRI, SODA, 160#, TNK FTG, 1/4F-CV OUT, 2000#, SM BLACK BONNET
	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005			SIZE DWG. NO. A 3741_SALES
			REV C
SCALE: 1:2		DO NOT SCALE DRAWING	SHEET 1 OF 1