



TANK GAUGE
(0-2000 PSI)

LOW PRESSURE GAUGE
(0-60 PSI)

SAFETY

INLET:
CGA 320
CO2 TANK FITTING

(7")

CGA 320 NUT (1-1/8 HEX)

OUTLET:
5/16 BARB SHUTOFF
WITH CHECK VALVE

(7")

NOTES:

1. SAFETY BLOW-OFF: 60 ± 5 PSI
2. WORKING PRESSURE: 0-50 PSI
3. SMALL BLACK ZINC BONNET

MATERIAL	NAME	DATE
	DRAWN	JPK 07/12/11
FINISH	ENG APPR.	
	PROPRIETARY AND CONFIDENTIAL	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



TITLE:
**REG, PRI, BEER, 60#, TANK
FTG, 5/16B-CV SHUTOFF,
2000#, SM BLACK, UL GAUGES**

SIZE	DWG. NO.	REV
A	3741-BR_SALES	C

SCALE: 1:2 DO NOT SCALE DRAWING SHEET 1 OF 1